

SPECIFICATION (EWX9500)

Rated line pull	9500 lbs (4309 kgs)		
Motor: series wound	12V:Input: 4.6kW / 6.1hp; Output: 2.1kW / 2.8hp 24V:Input: 6.5kW / 8.7hp; Output: 2.8kW / 3.8hp		
Gear reduction ratio	230:1		
Cable (Dia. × L)	Ø3/8" × 85 ' (Ø9.2mm × 26m)		
Drum size (Dia. × L)	Ø2.48 " × 8.8 " (Ø63mm × 223 mm)		
Mounting bolt pattern	10 " × 4.5 " (254mm × 114.3 mm) 4-M10		
Item	EWX9500U	EWX9500S	EWX9500F
Overall dimensions (L × W × H)	21.3" × 6.3" × 10.0" 540mm × 160mm × 254mm	21.3" × 6.3" × 11.1" 540mm × 160mm × 283mm	21.3" × 6.5" × 9.9" 540mm × 166mm × 251mm
Net weight lbs(kgs)	80.7 36.6	81.7 37.1	86.5 39.2

Pull, Speed, Amperes, Volts (First layer):

Line Pull	Line Speed ft/min (m/min)		Current A	
	12V DC	24V DC	12V DC	24V DC
lbs (kgs)				
0	19.7 (6.0)	22.3 (6.8)	80	70
3000(1361)	12.5 (3.8)	16.4(5.0)	170	140
6000(2722)	9.8 (3.0)	12.8 (3.9)	260	210
9500(4309)	6.2 (1.9)	9.5(2.9)	380	270

Line Pull And Rope Capacity In Layer

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	9500(4309)	17.4(5.3)
2	7706(3495)	39.4(12.0)
3	6482(2940)	65.0(19.8)
4	5593(2537)	85.3(26.0)